

Light in Detail

detay
LIGHTING

2023 CATALOG

detay LIGHTING

Established in 1993 in Istanbul, Detay Lighting operates in the production, sales and export of LED lighting luminaires. Detay Lighting continues its lighting journey with the vision of becoming one of the most successful companies in the lighting industry by increasing its brand value day by day.

The professional management staff, continuously developed sales channels, technical project network and the continuity of training of the sales team make a great contribution to this success.

At the same time, Detay Lighting, which provides services in the project department with its professional team of engineers and technicians, evaluates the projects on site and offers consultancy services to its customers in training and related fields.



INDEX

ROAD LIGHTING

7-18

| | |
|--------|---------|
| LEGEND | PALMA |
| HARE | MARTE |
| FERİS | BOLSENA |
| ZORA | PETRA |
| AYZA | CARMEN |
| NERA | SAKURA |



FLOODLIGHT

20-29

| | |
|-------|-------|
| TOKYO | DAKAR |
| PARİS | SAMAR |
| TİRAN | |



FACADE LIGHTING

30-33

GARDA



INDUSTRIAL LIGHTING

34-43

| | |
|-------|---------|
| LOFT | LONA |
| HELIX | NOVA |
| ZENNA | AKRA |
| TUNA | ARGENTO |
| BEGNA | ALİN |



CANOPY LIGHTING

44-45

QUADRO
TONOS



INDOOR LIGHTING

46-58

| | |
|---------|-------|
| MARİDE | SUDE |
| MARDE | ENJOY |
| TERRA | JOKER |
| DİRİTTO | CROSS |
| ENNA | ORION |



MODERN CITY LIGHTING

57-77

| | |
|--------|--------|
| VIA | TOTTO |
| PIANA | METRIT |
| PIENZA | WESER |
| MONA | ARNO |
| TOLL | WINNER |
| FAVEN | DARA |
| SMART | WONT |
| OTILE | |



INDEX





LEGEND



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, spirit level, circuit breaker, Ø42-60mm adjustable console, separate led module and tool-free accessible driver.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, photocell, nema socket, SPD, IP68 Connector.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.001 | 75W | 9750 | 3000-4000-6500K | 679x292x68 | 5,5 kg | 3 | 735x310x360 | 18,3 kg |
| | 100W | 13000 | 3000-4000-6500K | 679x292x68 | 5,7 kg | 3 | 735x310x360 | 19 kg |
| | 125W | 16250 | 3000-4000-6500K | 679x292x68 | 6,2 kg | 3 | 735x310x360 | 20,5 kg |
| | 150W | 19500 | 3000-4000-6500K | 679x292x68 | 6,2 kg | 3 | 735x310x360 | 20,5 kg |



HARE



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, spirit level, circuit breaker, Ø42-60mm adjustable console, separate led module and tool-free accessible driver.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, photocell, nema socket, SPD, IP68 Connector.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.002 | 200W | 26000 | 3000-4000-6500K | 793x337x70 | 6,5 kg | 3 | 820x376x375 | 22 kg |
| | 240W | 31200 | 3000-4000-6500K | 793x337x70 | 6,6 kg | 3 | 820x376x375 | 22,25 kg |



FERİS



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, spirit level, circuit breaker, Ø42-60mm adjustable console, separate led module and tool-free accessible driver.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS



Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, photocell, nema socket, SPD, IP68 Connector.



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.003 | 60W | 7800 | 3000-4000-6500K | 609x279x76 | 4 kg | 4 | 410x306x670 | 18,3 kg |
| | 75W | 9750 | 3000-4000-6500K | 609x279x76 | 4 kg | 4 | 410x306x670 | 18,3 kg |
| | 100W | 13000 | 3000-4000-6500K | 609x279x76 | 4 kg | 4 | 410x306x670 | 18,3 kg |
| | 125W | 16250 | 3000-4000-6500K | 609x279x76 | 4 kg | 4 | 410x306x670 | 18,3 kg |
| | 150W | 19500 | 3000-4000-6500K | 609x279x76 | 4 kg | 4 | 410x306x670 | 18,3 kg |



ZORA



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, spirit level, Ø42-60mm adjustable console.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, photocell, nema socket, IP68 Connector, SPD.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.004 | 60W | 7200 | 3000-4000-6500K | 519x172x67 | 3,5 kg | 4 | 460x300x220 | 15,6 kg |
| | 75W | 9000 | 3000-4000-6500K | 519x172x67 | 3,5 kg | 4 | 460x300x220 | 15,6 kg |
| | 100W | 12000 | 3000-4000-6500K | 519x172x67 | 3,5 kg | 4 | 460x300x220 | 15,6 kg |
| | 125W | 15000 | 3000-4000-6500K | 573x264x67 | 4 kg | 4 | 520x300x280 | 18,5 kg |
| | 150W | 18000 | 3000-4000-6500K | 573x264x67 | 4 kg | 4 | 520x300x280 | 18,5 kg |



NERA



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, spirit level, Ø42-60mm fixed console.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, photocell, nema socket, IP68 Connector, SPD.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l x w x h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|------------------------------|--------|---------------|-------------------|---------------------|
| DTY.005 | 60W | 7200 | 3000-4000-6500K | 438x205x67 | 3,5 kg | 4 | 460x300x220 | 15,6 kg |
| | 75W | 9000 | 3000-4000-6500K | 438x205x67 | 3,5 kg | 4 | 460x300x220 | 15,6 kg |
| | 100W | 12000 | 3000-4000-6500K | 438x205x67 | 3,5 kg | 4 | 460x300x220 | 15,6 kg |
| | 125W | 15000 | 3000-4000-6500K | 501x265x67 | 4 kg | 4 | 520x300x280 | 18,5 kg |
| | 150W | 18000 | 3000-4000-6500K | 501x265x67 | 4 kg | 4 | 520x300x280 | 18,5 kg |



AYZA



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, Ø42-48mm fixed console, seperate led module and tool-free accessible driver.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 88% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, photocell, nema socket, SPD, IP68 Connector.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.006 | 25W | 3250 | 3000-4000-6500K | 372x212x67 | 2,2 kg | 6 | 560x240x430 | 15 kg |
| | 50W | 6500 | 3000-4000-6500K | 372x212x67 | 2,2 kg | 6 | 560x240x430 | 15 kg |
| | 60W | 7800 | 3000-4000-6500K | 372x212x67 | 2,2 kg | 6 | 560x240x430 | 15 kg |



PALMA



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, spirit level, Ø42-48mm fixed console.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER


Constant current output, With 88% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|---------|---------------|-------------------|---------------------|
| DTY.007 | 30W | 3600 | 3000-4000-6500K | 261x150x56 | 1,25 kg | 12 | 470x240x160 | 17,6 kg |
| | 50W | 6000 | 3000-4000-6500K | 261x150x56 | 1,25 kg | 12 | 470x240x160 | 17,6 kg |



MARTE



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, Ø42-60mm fixed console.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, SPD, IP68 Connector, 20W Decorative Light



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|---------|---------------|----------------|------------------|
| DTY.008 | 60W | 7800 | 3000-4000-6500K | 525x425x110 | 5,5 kg | 4 | 470x470x660 | 25 kg |
| | 75W | 9750 | 3000-4000-6500K | 525x425x110 | 5,5 kg | 4 | 470x470x660 | 25 kg |
| | 100W | 13000 | 3000-4000-6500K | 525x425x110 | 5,75 kg | 4 | 470x470x660 | 26 kg |
| | 125W | 16250 | 3000-4000-6500K | 525x425x110 | 5,75 kg | 4 | 470x470x660 | 26 kg |



BOLSENA



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, SPD, IP68 Connector, 20W Decorative Light.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|----------------|------------------|
| DTY.010 | 60W | 7800 | 3000-4000-6500K | Ø425x110 | 5,2 kg | 4 | 470x470x660 | 24 kg |
| | 75W | 9750 | 3000-4000-6500K | Ø425x110 | 5,2 kg | 4 | 470x470x660 | 24 kg |
| | 100W | 13000 | 3000-4000-6500K | Ø425x110 | 5,4 kg | 4 | 470x470x660 | 24,5 kg |
| | 125W | 16250 | 3000-4000-6500K | Ø425x110 | 5,4 kg | 4 | 470x470x660 | 24,5 kg |



PETRA



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, Ø42-60mm adjustable console.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS



Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, SPD, IP68 Connector.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|---------|---------------|----------------|------------------|
| DTY.009 | 60W | 7800 | 3000-4000-6500K | 645x450x88 | 5,5 kg | 4 | 470x470x660 | 25 kg |
| | 75W | 9750 | 3000-4000-6500K | 645x450x88 | 5,5 kg | 4 | 470x470x660 | 25 kg |
| | 100W | 13000 | 3000-4000-6500K | 645x450x88 | 5,75 kg | 4 | 470x470x660 | 26 kg |



CARMEN



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, SPD, IP68 Connector.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|----------------|------------------|
| DTY.011 | 60W | 7800 | 3000-4000-6500K | Ø450x88 | 5,2 kg | 4 | 470x470x660 | 24 kg |
| | 75W | 9750 | 3000-4000-6500K | Ø450x88 | 5,2 kg | 4 | 470x470x660 | 24 kg |
| | 100W | 13000 | 3000-4000-6500K | Ø450x88 | 5,4 kg | 4 | 470x470x660 | 24,5 kg |



SAKURA TUNNEL LIGHTING



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certificated IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

Dimmable, programmable, DALI driver, SPD, IP68 Connector.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.012 | 60W | 7800 | 3000-4000-6500K | 507x224x195 | 8 kg | 3 | 540x266x540 | 26 kg |
| | 75W | 9750 | 3000-4000-6500K | 507x224x195 | 8 kg | 3 | 540x266x540 | 26 kg |
| | 100W | 13000 | 3000-4000-6500K | 507x224x195 | 8 kg | 3 | 540x266x540 | 26 kg |
| | 150W | 19500 | 3000-4000-6500K | 507x224x195 | 8 kg | 3 | 540x266x540 | 26 kg |
| | 240W | 31200 | 3000-4000-6500K | 507x224x195 | 8 kg | 3 | 540x266x540 | 26 kg |
| | 320W | 41600 | 3000-4000-6500K | 507x224x195 | 8,2 kg | 3 | 540x266x540 | 26,5 kg |



İstanbul Ataköy Kapalı Atletizm Salonu
projesinde 1200 Watt Tokyo projektör kullanıldı.



TOKYO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, dimmable-programmable ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.013 | 240W | 31200 | 3000-4000-6500K | 280x507x150 | 8,3 kg | 3 | 540x266x540 | 26,5 kg |
| | 320W | 41600 | 3000-4000-6500K | 280x507x150 | 8,5 kg | 3 | 540x266x540 | 27 kg |
| | 240W* | 28800 | 3000-4000-6500K | 280x507x150 | 8,3 kg | 3 | 540x266x540 | 26,5 kg |
| | 320W* | 38400 | 3000-4000-6500K | 280x507x150 | 8,5 kg | 3 | 540x266x540 | 27 kg |

*for 3535 LED version



TOKYO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, dimmable-programmable ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens or *PC reflector with aluminium reflective coating.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|---------|---------------|----------------|------------------|
| DTY.013 | 400W | 52000 | 3000-4000-6500K | 332x554x215 | 12 kg | 3 | 580x300x580 | 37 kg |
| | 500W | 65000 | 3000-4000-6500K | 332x554x215 | 12,5 kg | 3 | 580x300x580 | 38,5 kg |
| | 400W* | 48000 | 3000-4000-6500K | 332x554x215 | 12 kg | 3 | 580x300x580 | 37 kg |
| | 500W* | 60000 | 3000-4000-6500K | 332x554x215 | 12,5 kg | 3 | 580x300x580 | 38,5 kg |

*for 80 CRI 3535 LED version

FLOODLIGHT



TOKYO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, dimmable-programmable ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens or *PC reflector with aluminium reflective coating.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

SPD IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| | | |
|----------|----------|----------|
| Standard | Optional | Optional |
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|--------|--------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.013 | 800W | 104000 | 3000-4000-6500K | 607x554x285 | 24 kg | 1 | 630x560x300 | 25 kg |
| | 1000W | 130000 | 3000-4000-6500K | 607x554x285 | 25 kg | 1 | 630x560x300 | 26 kg |
| | 800W* | 96000 | 3000-4000-6500K | 607x554x285 | 24 kg | 1 | 630x560x300 | 25 kg |
| | 1000W* | 120000 | 3000-4000-6500K | 607x554x285 | 25 kg | 1 | 630x560x300 | 26 kg |

*for 80 CRI 3535 LED version



TOKYO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, dimmable-programmable ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens or *PC reflector with aluminium reflective coating.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|--------|--------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.013 | 1200W | 156000 | 3000-4000-6500K | 892x554x285 | 36 kg | 1 | 920x560x300 | 37 kg |
| | 1500W | 195000 | 3000-4000-6500K | 892x554x285 | 38 kg | 1 | 920x560x300 | 39 kg |
| | 1200W* | 144000 | 3000-4000-6500K | 892x554x285 | 36 kg | 1 | 920x560x300 | 37 kg |
| | 1500W* | 180000 | 3000-4000-6500K | 892x554x285 | 38 kg | 1 | 920x560x300 | 39 kg |

*for 80 CRI 3535 LED version



TOKYO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, dimmable-programmable ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens or *PC reflector with aluminium reflective coating.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| | | |
|----------|----------|----------|
| Standard | Optional | Optional |
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.013 | 600W | 78000 | 3000-4000-6500K | 507x438x217 | 15 kg | 1 | 530x460x240 | 16 kg |
| | 600W* | 72000 | 3000-4000-6500K | 507x438x217 | 15 kg | 1 | 530x460x240 | 16 kg |

*for 80 CRI 3535 LED version



TOKYO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, dimmable-programmable ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens or *PC reflector with aluminium reflective coating.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|--------|--------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.013 | 1200W | 156000 | 3000-4000-6500K | 507x851x220 | 32 kg | 1 | 530x900x240 | 33 kg |
| | 1200W* | 14400 | 3000-4000-6500K | 507x851x220 | 32 kg | 1 | 530x900x240 | 33 kg |

*for 80 CRI 3535 LED version



PARIS



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable driver, SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.014 | 100W | 13000 | 3000-4000-6500K | 386x320x63 | 4,4 kg | 4 | 375x346x395 | 19,3 kg |
| | 125W | 16250 | 3000-4000-6500K | 386x320x63 | 4,4 kg | 4 | 375x346x395 | 19,3 kg |
| | 150W | 19500 | 3000-4000-6500K | 386x320x63 | 4,4 kg | 4 | 375x346x395 | 19,3 kg |
| | 200W | 26000 | 3000-4000-6500K | 421x360x62 | 5,3 kg | 4 | 420x360x450 | 23 kg |



TIRAN



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable driver, SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.015 | 30W | 3900 | 3000-4000-6500K | 250x170x46 | 1,2 kg | 12 | 550x250x200 | 17 kg |
| | 50W | 6500 | 3000-4000-6500K | 253x205x46 | 1,8 kg | 10 | 550x250x200 | 21 kg |
| | 60W | 7800 | 3000-4000-6500K | 253x205x46 | 1,8 kg | 10 | 550x250x200 | 21 kg |
| | 75W | 9750 | 3000-4000-6500K | 253x205x46 | 1,8 kg | 10 | 550x250x200 | 21 kg |

FLOODLIGHT



DAKAR



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 88% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certificated IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

Dimmable, programmable driver, SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.016 | 30W | 3900 | 3000-4000-6500K | 349x220x90 | 2,5 kg | 6 | 545x256x400 | 16,5 kg |
| | 50W | 6500 | 3000-4000-6500K | 349x220x90 | 2,5 kg | 6 | 545x256x400 | 16,5 kg |
| | 60W | 7800 | 3000-4000-6500K | 349x220x90 | 2,5 kg | 6 | 545x256x400 | 16,5 kg |



SAMAR



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certified IP67 Driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable driver, SPD, IP68 Connector.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.017 | 60W | 7800 | 3000-4000-6500K | 319x290x171 | 2,8 kg | 4 | 700x360x365 | 13,25 kg |
| | 75W | 9750 | 3000-4000-6500K | 319x290x171 | 2,8 kg | 4 | 700x360x365 | 13,25 kg |
| | 100W | 13000 | 3000-4000-6500K | 319x290x171 | 2,8 kg | 4 | 700x360x365 | 13,25 kg |



GARDA I



BODY

Aluminium eloxal coated extrusion body, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 88% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

IP68 Connector.



TECHNICAL SPECIFICATIONS



SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|---------|--------------------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.018 | 8W | 880 | 3000-4000-6500K | 190x70x155 | 0,7 kg | 12 | 560x240x430 | 11 kg |
| | 8W | 120-520 | Amber - Kırmızı - Mavi - Yeşil | 190x70x155 | 0,7 kg | 12 | 560x240x430 | 11 kg |



GARDA II



BODY

Aluminium eloxal coated extrusion body, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 88% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


IP68 Connector.



TECHNICAL SPECIFICATIONS



SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|----------|-----------------------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.018 | 15W | 1650 | 3000-4000-6500K | 340x70x155 | 1 kg | 12 | 560x240x430 | 14,7 kg |
| | 15W | 225-975 | Amber - Kırmızı - Mavi - Yeşil | 340x70x155 | 1 kg | 12 | 560x240x430 | 14,7 kg |
| | 20W | 2200 | 3000-4000-6500K | 340x70x155 | 1 kg | 12 | 560x240x430 | 14,7 kg |
| | 20W | 300-1300 | Amber - Kırmızı - Mavi - Yeşil | 340x70x155 | 1 kg | 12 | 560x240x430 | 14,7 kg |



GARDA III



BODY

Aluminium eloxal coated extrusion body, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 88% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


IP68 Connector.



TECHNICAL SPECIFICATIONS



SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|----------|--------------------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.018 | 25W | 2750 | 3000-4000-6500K | 660x70x155 | 1,7 kg | 8 | 1210x370x180 | 15,3 kg |
| | 25W | 375-1625 | Amber - Kırmızı - Mavi - Yeşil | 660x70x155 | 1,7 kg | 8 | 1210x370x180 | 15,3 kg |
| | 30W | 3300 | 3000-4000-6500K | 660x70x155 | 1,7 kg | 8 | 1210x370x180 | 15,3 kg |
| | 30W | 450-1950 | Amber - Kırmızı - Mavi - Yeşil | 660x70x155 | 1,7 kg | 8 | 1210x370x180 | 15,3 kg |



GARDA IV



BODY

Aluminium eloxal coated extrusion body, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 88% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


IP68 Connector.



TECHNICAL SPECIFICATIONS



SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|----------|-----------------------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.018 | 40W | 4400 | 3000-4000-6500K | 1000x70x155 | 2,8 kg | 8 | 1210x370x180 | 24,6 kg |
| | 40W | 600-2600 | Amber - Kırmızı - Mavi - Yeşil | 1000x70x155 | 2,8 kg | 8 | 1210x370x180 | 24,6 kg |



LOFT



BODY

Aluminium eloxal coated extrusion body, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage industrial driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS


DALI driver, 1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.019 | 75W | 9000 | 3000-4000-6500K | 650x95x104 | 2,9 kg | 6 | 680x335x250 | 19,8 kg |
| | 100W | 12000 | 3000-4000-6500K | 800x95x104 | 3,4 kg | 6 | 830x335x250 | 23,2 kg |
| | 125W | 15000 | 3000-4000-6500K | 950x95x104 | 4 kg | 6 | 980x335x250 | 27,2 kg |
| | 150W | 18000 | 3000-4000-6500K | 1250x95x104 | 5 kg | 4 | 1280x230x250 | 22,7 kg |
| | 200W | 24000 | 3000-4000-6500K | 1550x95x104 | 6,2 kg | 4 | 1580x230x250 | 27,8 kg |



HELIX



BODY

Aluminium eloxal coated extrusion body, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage industrial driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


DALI driver, 1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.020 | 75W | 9750 | 3000-4000-6500K | 500x195x132 | 3,6 kg | 5 | 530x455x430 | 19,75 kg |
| | 100W | 13000 | 3000-4000-6500K | 650x195x132 | 4,5 kg | 5 | 680x455x430 | 24,6 kg |
| | 125W | 16250 | 3000-4000-6500K | 800x195x132 | 5,5 kg | 4 | 830x430x310 | 24,4 kg |
| | 150W | 19500 | 3000-4000-6500K | 950x195x132 | 6,3 kg | 4 | 970x430x310 | 28,2 kg |
| | 200W | 26000 | 3000-4000-6500K | 1250x195x132 | 8 kg | 3 | 1280x455x225 | 27 kg |



ZENNA



BODY

Aluminium eloxal coated extrusion body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage industrial driver.

LENS


Resistant to UV rays, 90% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.021 | 75W | 9750 | 3000-4000-6500K | 600x110x37 | 3 kg | 6 | 650x400x280 | 20,5 kg |
| | 100W | 13000 | 3000-4000-6500K | 900x110x37 | 2,3 kg | 8 | 1260x340x220 | 21 kg |
| | 150W | 19500 | 3000-4000-6500K | 1200x110x37 | 2,3 kg | 8 | 1260x340x220 | 21 kg |



TUNA



BODY

Aluminium eloxal coated extrusion body, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage industrial driver.

LENS


Anodised aluminium reflector with high reflectivity.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.025 | 75W | 9750 | 3000-4000-6500K | 600x105x110 | 3 kg | 6 | 650x400x280 | 20,5 kg |
| | 100W | 13000 | 3000-4000-6500K | 750x105x110 | 4 kg | 6 | 800x400x280 | 27,5 kg |
| | 150W | 19500 | 3000-4000-6500K | 1150x105x110 | 5 kg | 4 | 1380x280x280 | 23 kg |
| | 220W | 28600 | 3000-4000-6500K | 1500x105x110 | 6 kg | 4 | 1550x280x280 | 27,6 kg |



BEGNA



BODY

Aluminium eloxal coated extrusion body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


PC extrusion opal cover.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, sensor with stepdim function.



TECHNICAL SPECIFICATIONS



SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.029 | 18W | 2160 | 3000-4000-6500K | 600x72x51 | 0,6 kg | 8 | 670x300x180 | 6,5 kg |
| | 35W | 4200 | 3000-4000-6500K | 1160x72x51 | 1,2 kg | 10 | 1210x370x180 | 14,1 kg |
| | 50W | 6000 | 3000-4000-6500K | 1500x72x51 | 1,5 kg | 12 | 1650x385x265 | 23,5 kg |
| | 65W | 7800 | 3000-4000-6500K | 1500x72x51 | 1,5 kg | 12 | 1650x385x265 | 23,5 kg |



LONA



BODY

PC co-extrusion body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER


Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, sensor with stepdim function.



TECHNICAL SPECIFICATIONS



SYMMETRIC




| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.030 | 18W | 2160 | 3000-4000-6500K | 600x72x52 | 0,5 kg | 8 | 670x300x180 | 5,7 kg |
| | 35W | 4200 | 3000-4000-6500K | 1160x72x52 | 0,8 kg | 10 | 1210x370x180 | 10,5 kg |
| | 50W | 6000 | 3000-4000-6500K | 1500x72x52 | 1,5 kg | 12 | 1650x385x265 | 23,5 kg |




NOVA



- BODY**
Aluminium injection body, electrostatic powder coated.
- LED**
100.000 hours LED lifetime according to LM-80 and TM-21 report.
- DRIVER**
Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.
- LENS**
Resistant to UV rays, 90% optically efficient PC material IP65 lens.
- PCB**
Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.
- OPTIONS**
1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



RAL CODES

| | | |
|----------|----------|----------|
| Standard | Optional | Optional |
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC

| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|----------------|------------------|
| DTY.024 | 150W | 18000 | 3000-4000-6500K | Ø349X156 | 2,8 kg | 4 | 720X366X370 | 14 kg |
| | 200W | 24000 | 3000-4000-6500K | Ø349X156 | 3 kg | 4 | 720X366X370 | 14,5 kg |



AKRA



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS



Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



RAL CODES

Standard




Optional



Optional



SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|----------------|------------------|
| DTY.023 | 60W | 7800 | 3000-4000-6500K | Ø282x90 | 2,2 kg | 4 | 580x296x315 | 10,5 kg |
| | 75W | 9750 | 3000-4000-6500K | Ø282x90 | 2,4 kg | 4 | 580x296x315 | 11 kg |
| | 100W | 13000 | 3000-4000-6500K | Ø282x90 | 2,4 kg | 4 | 580x296x315 | 11 kg |



ARGENTO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

1-3 hours emergency kit.




TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.022 | 75W | 9750 | 3000-4000-6500K | 335x335x150 | 4 kg | 4 | 700x360x365 | 18,5 kg |
| | 100W | 13000 | 3000-4000-6500K | 335x335x150 | 4 kg | 4 | 700x360x365 | 18,5 kg |
| | 125W | 16250 | 3000-4000-6500K | 335x335x150 | 4,2 kg | 4 | 700x360x365 | 19 kg |
| | 150W | 19500 | 3000-4000-6500K | 335x335x150 | 4,2 kg | 4 | 700x360x365 | 19 kg |



ALIN



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage, ENEC certificated IP67 driver.

LENS


Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

1-3 hours emergency kit.




TECHNICAL SPECIFICATIONS




RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|----------------|------------------|
| DTY.028 | 200W | 26000 | 3000-4000-6500K | 507x224x195 | 8 kg | 3 | 540x266x540 | 26 kg |
| | 240W | 31200 | 3000-4000-6500K | 507x224x195 | 8 kg | 3 | 540x266x540 | 26 kg |
| | 320W | 41600 | 3000-4000-6500K | 507x224x195 | 8,2 kg | 3 | 540x266x540 | 26,5 kg |



QUADRO



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS



Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable driver.




TECHNICAL SPECIFICATIONS



RAL CODES

Standard
RAL
9016

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|--------------------------|--------|---------------|-------------------|---------------------|
| DTY.031 | 75W | 9750 | 3000-4000-6500K | 425x425x150 | 5,3 kg | 4 | 470x470x660 | 24 kg |
| | 100W | 13000 | 3000-4000-6500K | 425x425x150 | 5,3 kg | 4 | 470x470x660 | 24 kg |
| | 125W | 16250 | 3000-4000-6500K | 425x425x150 | 5,3 kg | 4 | 470x470x660 | 24 kg |
| | 150W | 19500 | 3000-4000-6500K | 425x425x150 | 5,3 kg | 4 | 470x470x660 | 24 kg |



TONOS



BODY

Aluminium injection body, electrostatic powder coated, 4mm tempered glass, ventilation plug.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS



Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

Dimmable, programmable driver.




TECHNICAL SPECIFICATIONS



RAL CODES

Standard
RAL
9016

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces | Outer Box (mm) | Outer Box Weight |
|--------------|-------|-------|-------------------|------------------------|--------|---------------|-------------------|---------------------|
| DTY.032 | 75W | 9750 | 3000-4000-6500K | Ø450x88 | 5,2 kg | 4 | 470x470x660 | 24 kg |
| | 100W | 13000 | 3000-4000-6500K | Ø450x88 | 5,2 kg | 4 | 470x470x660 | 24 kg |



MARİDE

CLIP-IN



BODY

DKP sheet body with electrostatic powder coated.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


FR4 PCB 1 mm. Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



RAL CODES

Optional

RAL
9016

SYMMETRIC



120°

| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|
| DTY.033 | 15W | 1650 | 3000-4000-6500K | 300x300x55 | 1 kg | 6 |
| | 35W | 3850 | 3000-4000-6500K | 600x600x55 | 2,5 kg | 6 |



MARDE SURFACE



BODY

ABS material body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


FR4 PCB 1 mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|
| DTY.034 | 35W | 3850 | 3000-4000-6500K | 650x650x60 | 2,5 kg | 8 |



TERRA



BODY

Aluminium injection body, electrostatic powder coated.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9022 | RAL 9016 | RAL 9005 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Hole Diameter | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|---------------|--------|---------------|
| DTY.035 | 10W | 1100 | 3000-4000-6500K | Ø119x44 | 105 | 0,3 kg | 6 |
| | 15W | 1650 | 3000-4000-6500K | Ø147x44 | 130 | 1 kg | 6 |
| | 20W | 2200 | 3000-4000-6500K | Ø178x44 | 155 | 1 kg | 6 |
| | 30W | 3300 | 3000-4000-6500K | Ø228x44 | 210 | 1,3 kg | 6 |



DIRITTO



BODY

Electrostatic powder coated, extrusion body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


PC extrusion opal cover.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, colour and length options upon request.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|
| DTY.036 | 18W | 1980 | 3000-4000-6500K | 560x70x50 | 1 kg | 6 |
| | 35W | 3850 | 3000-4000-6500K | 1120x70x50 | 1,6 kg | 6 |
| | 50W | 5500 | 3000-4000-6500K | 1500x70x50 | 2 kg | 6 |



ENNA



BODY

Electrostatic powder coated, extrusion body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


PC extrusion opal cover.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, colour and length options upon request.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|
| DTY.037 | 18W | 1980 | 3000-4000-6500K | 560x70x50 | 1 kg | 6 |
| | 35W | 3850 | 3000-4000-6500K | 1120x70x50 | 1,4 kg | 6 |
| | 50W | 5500 | 3000-4000-6500K | 1500x70x50 | 2 kg | 6 |



SUDE



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, colour and length options upon request.



TECHNICAL SPECIFICATIONS



RAL CODES

Standard

RAL
9005

Optional

RAL
9016

Optional

RAL
9022

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|
| DTY.038 | 35W | 3850 | 3000-4000-6500K | 1000x80x80 | 1,5 kg | 6 |
| | 50W | 5500 | 3000-4000-6500K | 1200x80x80 | 3,5 kg | 6 |
| | 65W | 7150 | 3000-4000-6500K | 1500x80x80 | 4 kg | 6 |



ENJOY



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, colour and length options upon request.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.039 | 45W | 4950 | 3000-4000-6500K | Ø600x100 | 3 kg | 6 |
| | 65W | 7150 | 3000-4000-6500K | Ø900x100 | 4 kg | 6 |
| | 75W | 8250 | 3000-4000-6500K | Ø1200x100 | 6 kg | 6 |



JOKER



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ,HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, colour and length options upon request.



TECHNICAL SPECIFICATIONS



RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.040 | 40W | 4400 | 3000-4000-6500K | Ø400x100 | 3 kg | 6 |
| | 60W | 6600 | 3000-4000-6500K | Ø600x100 | 4 kg | 6 |
| | 100W | 11000 | 3000-4000-6500K | Ø900x100 | 6 kg | 6 |



CROSS



BODY

Electrostatic powder coated, extrusion body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, colour and length options upon request.



TECHNICAL SPECIFICATIONS



RAL CODES

Standard

RAL 9005

Optional

RAL 9016

Optional

RAL 9022

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|
| DTY.041 | 40W | 4400 | 3000-4000-6500K | 400x400x80 | 3 kg | 6 |
| | 75W | 8250 | 3000-4000-6500K | 600x600x80 | 4 kg | 6 |
| | 100W | 11000 | 3000-4000-6500K | 900x900x80 | 6 kg | 6 |



ORION



BODY

Electrostatic powder coated, extrusion body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS


Opal diffuser.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS

DALI driver, 1-3 hours emergency kit, colour and length options upon request.



TECHNICAL SPECIFICATIONS



RAL CODES


| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 9005 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions l w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|-----------------------|--------|---------------|
| DTY.042 | 40W | 4400 | 3000-4000-6500K | 400x347x80 | 3 kg | 6 |
| | 60W | 6600 | 3000-4000-6500K | 600x347x80 | 4 kg | 6 |
| | 75W | 8250 | 3000-4000-6500K | 900x347x80 | 6 kg | 6 |





VIA



BODY

Electrostatic powder coated aluminium body, galvanised steel pole.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Opal Diffuser.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.048 | 60W | 6000 | 3000-6500K | Ø560x3200 | 20 kg | 1 |
| | 60W | 6000 | 3000-6500K | Ø560x4200 | 25 kg | 1 |



MONA I



BODY

Electrostatic powder coated aluminium body, galvanised steel pole, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS



Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.049 | 60W | 7800 | 3000-6500K | Ø450x3500 | 22 kg | 1 |



MONA II



BODY

Electrostatic powder coated aluminium body, galvanised steel pole, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.049 | 60W | 7800 | 3000-6500K | Ø450x3500 | 22 kg | 1 |



PIANA



BODY

Electrostatic powder coated aluminium body, galvanised steel pole, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.051 | 50W | 6000 | 3000-6500K | Ø450x3000 | 18 kg | 1 |



PIENZA



BODY

Electrostatic powder coated aluminium body, galvanised steel pole, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver, 20W visual light.

TECHNICAL SPECIFICATIONS


RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|--------|-------|-------------------|---------------------|--------|---------------|
| DTY.050 | 60W | 7800 | 3000-6500K | Ø425x3500 | 22 kg | 1 |
| | 60+20W | 7800 | 3000-6500K | Ø425x3500 | 22 kg | 1 |



TOLL



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.053 | 50W | 6000 | 3000-6500K | 200x200x3000 | 16 kg | 1 |



FAVEN



BODY

Electrostatic powder coated aluminium body, galvanised steel pole, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.054 | 60W | 7800 | 3000-6500K | 700x3000 | 16 kg | 1 |



SMART I



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS


RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.043 | 30W | 3900 | 3000-6500K | 600x3000 | 12 kg | 1 |



SMART II



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.043 | 2*30W | 7800 | 3000-6500K | 1200x4000 | 17 kg | 1 |



OTILE



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.044 | 2*30W | 7800 | 3000-6500K | 500x4000 | 15 kg | 1 |



TOTTO



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.046 | 2*30W | 7800 | 3000-6500K | 1200x6000 | 35 kg | 1 |



METRIT I



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS


RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.045 | 30W | 3900 | 3000-6500K | 400x3000 | 12 kg | 1 |



METRIT II



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.045 | 30*2W | 7800 | 3000-6500K | 800x3000 | 17 kg | 1 |



WESER I



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.047 | 30W | 3900 | 3000-6500K | 700x3500 | 15 kg | 1 |



WESER II



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.047 | 2*30W | 7800 | 3000-6500K | 1400x4000 | 20 kg | 1 |



ARNO I



BODY

Electrostatic powder coated aluminium body, galvanised steel pole, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.052 | 60W | 7800 | 3000-6500K | 600x4000 | 35 kg | 1 |

ARNO II



BODY

Electrostatic powder coated aluminium body, galvanised steel pole, 4mm tempered glass.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 93% optically efficient PMMA material lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm. Copper Thickness: 1 OZ, HASL surface coating.

OPTIONS


Programmable driver.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.052 | 2*60W | 15600 | 3000-6500K | 1200x6000 | 50 kg | 1 |

WINNER



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

IP65 glass lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.




TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|---------|---------------|
| DTY.056 | 12W | 1400 | 3000-6500K | 100x100x200 | 1,75 kg | 1 |
| | 12W | 1400 | 3000-6500K | 100x100x400 | 2 kg | 1 |
| | 12W | 1400 | 3000-6500K | 100x100x600 | 2,5 kg | 1 |
| | 12W | 1400 | 3000-6500K | 100x100x800 | 3 kg | 1 |

DARA



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.




TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions d h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.055 | 10W | 1200 | 3000-6500K | Ø125x400 | 2 kg | 1 |
| | 10W | 1200 | 3000-6500K | Ø125x600 | 2,5 kg | 1 |
| | 10W | 1200 | 3000-6500K | Ø125x800 | 3 kg | 1 |

WONT I-II



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB

Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.




TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.057 | 12W | 1440 | 3000-6500K | 105x200x600 | 2 kg | 1 |
| | 12W | 1440 | 3000-6500K | 105x200x800 | 2,5 kg | 1 |
| | 2*12W | 2880 | 3000-6500K | 200x350x800 | 2 kg | 1 |
| | 2*12W | 2880 | 3000-6500K | 200x350x800 | 2,5 kg | 1 |

WONT III-IV



BODY

Electrostatic powder coated aluminium body.

LED

100.000 hours LED lifetime according to LM-80 and TM-21 report.

DRIVER

Constant current output, With 90% efficiency, Effective power factor regulation that is not affected by fluctuations in grid voltage.

LENS

Resistant to UV rays, 90% optically efficient PMMA/ PC material IP65 lens.

PCB


Aluminum PCB, Aluminum Base Layer / Thickness: 1L / 1.6mm.
Copper Thickness: 1 OZ, HASL surface coating.

TECHNICAL SPECIFICATIONS

RAL CODES

| Standard | Optional | Optional |
|----------|----------|----------|
| RAL 7016 | RAL 9016 | RAL 9022 |

SYMMETRIC / ASYMMETRIC



| Product Code | Power | Lumen | Color Temperature | Dimensions w h (mm) | Weight | Carton Pieces |
|--------------|-------|-------|-------------------|---------------------|--------|---------------|
| DTY.057 | 12W | 1440 | 3000-6500K | 156x100x863 | 3 kg | 1 |
| | 2*12W | 2880 | 3000-6500K | 263x100x863 | 4 kg | 1 |



detay
LIGHTING

www.detayaydinlatma.com.tr



Emek Mahallesi, Sırdaş Sokak
No: 27/1 Sancaktepe, İstanbul/Türkiye

Phone: +90 216 602 11 41
Export: export@detayaydinlatma.com.tr

Follow us from our social media accounts



[/detayaydinlatma](https://www.instagram.com/detayaydinlatma)



[/DetayAydinlatma](https://www.facebook.com/DetayAydinlatma)



[detaylighting](https://www.linkedin.com/company/detaylighting)